

## 35" pure stock (page 1)

Engine-	Must be:	original equip. for make(ford in ford, chevy in chevy). Motor type location. cast iron block & heads.
v-8	Allowed:	big block in half ton and heavier trucks. Aluminum intake. V-8 in any truck that offered a from factory.
trucks	Not allowed:	relocating engine. Aluminum heads. Aluminum block. Big blocks in any mini/compact
Carburetion-	Must be:	single carb or stock efi if applicable to make & model
	Allowed:	aluminum intake & spacers, aftermarket carburetors.
	Not allowed:	after market injection. Blowers. Superchargers.
Body (interior)-	Must be:	firewall & floorboard in stock location & made of factory type material. All interior panels, seats & all dash intact in cab.
	Allowed:	Race seats & race harnesses.
	Not allowed:	cutting & gutting. Loose items.
Body (exterior)-	must be:	full body vehicles. All lights & glass must be present.
	Allowed:	removal of body parts that can be removed; top of jeep, blazer etc. with same features may be removed. Fender trim for tire fitment only. Flat bed(has to be able to support 300 lbs at any point on bed)
	Not allowed:	lexan windows. Cutting & gutting. Body swaps. Fiberglass bodies.
Frame:	must be:	o.e. stock frame that matches make of body.
	Not allowed:	modified frames. Cutting. Tube frames.
Axles-	must be:	in stock location & fender well location.
	Allowed:	axle upgrade
	Not allowed:	wheel base alterations
Suspension-	must be:	stock
	Allowed:	lift kits- ladder bars
	Not allowed:	coil over shocks. 3 & 4 link suspension. Floating suspension. Relocating.
Drive train-	must be:	stock transfer case. Stock transmission.
	Not allowed:	aftermarket transfer case or chain drives.
Exhaust-	must be:	full exhaust. 12" minimum muffler. Pipes come within 1 foot of rear axle or 18" past drivers compartment.
	Allowed:	up to 3 ½ " max diameter exhaust pipe. Headers.
	Not allowed:	open exhaust or Dumps.

## 35" pure stock (page 2)

Fuel-	must be:	unleaded pump gas only.
	Allowed:	fuel cells. 3/8 fuel line or smaller.
	Not allowed:	race fuel. Alcohol. Will check for dye. No nitrous. Regulators. Adjustable fuel logs.
Fuel pump-	must be:	stock manual fuel pump only.
	Allowed:	stock efi fuel pump running stock efi.
	Not allowed:	efi fuel pump assisting manual fuel pump or anything besides stock efi. Regulators. Adjustable fuel logs.
Tires-	must be:	35" & below dot
	Allowed:	dot tires measuring up to 35"
	Not allowed:	cut tires. Modified tires. Ag tires. Paddle tires.
Brakes-	must be:	have all 4 brakes on both axles & in working order.
	Not allowed:	trans brake braking system & driveline brakes. Transmission break.
Additional-	must be:	battery in stock location. Radiator in stock location. All topless vehicles must have roll cage & five point harness.
	Roll cage exemption:	any truck that qualifies for pure stock 35" class or 38.5" class does not have to have roll cage. Can only change tires to run upper classes.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
		* see general rules