

## **44" super modified mens <44" super modified womens-same as men except woman driver> (page 1)**

Engine-	must be:	natural aspirated.
	Allowed:	Aluminum heads. Intake. Block.
	Not allowed:	harmonic balancer cannot be behind front axle tube
Carburetion-	must be:	natural aspirated
	Allowed:	nitrous. Aftermarket injection. Aftermarket carburetors. Dual carbs
	Not allowed:	aftermarket turbos. Blowers. Superchargers.
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	cab & o.e. frame minimum. Must resemble a vehicle.
	Allowed:	cutting & gutting
	Not allowed:	loose items
Frame-	must be:	o.e. frame
	Allowed:	lightning of frame
	Not allowed:	Tube frame.
Axles-	must be:	any type. Front axle cannot be in front of harmonic balancer.
Suspension-	must be:	any type
Exhaust-	must be:	aimed away from spectators, officials
	Allowed:	open
Fuel-	must be:	safe & controlled
	Allowed:	any type
	Not allowed:	unsafe fuels
Tires-	must be:	44" & below dot
	Allowed:	44" & below dot
	Not allowed:	ag. Paddle. Cuts. Modified.
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes

## **44" super modified mens (44" super modified womens-same as men except woman driver)**

Drive train-	must be:	transfer case. Driveshaft loops. One per shaft.
	Allowed:	after market transfer case
	Not allowed:	chain drives
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame. Unsafe cage.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.

\* see general rules