

General rules

No unsportsmanlike conduct!

All convertible vehicles with no tops must have roll cage.

Vehicle entered one time per class

Seatbelts & helmets must be worn by driver & passenger. 4 point harness required in all classes excluding stock classes.

No kid passengers in any class besides stock class. No infants! Safety first.
No riders in the back of the truck

No hot Roding

Stay away from tractor & cable

No fighting

No refunds

Clevis or safe pullout point installed directly on vehicle. Chains are unacceptable.

All tires must be factory stamped & legible to run in any DOT only class.

If vehicle is unsafe to run the staff has the right to not let you run. Example: not able to stop.
Flaming up or spraying fluids.

Nitrous bottles will be removed from vehicles while running in classes which do not allow nitrous.

All tires must be rubber. No chains, cables or bolts on or in tires.

Disqualifications:

Helmets & safety harness must be worn during run. If not this will result in a disqualification.

Loose items: all items must be secured. Anything that comes out of vehicle will result in a disqualification.

Example: unsecured batteries, fuel cells or trash. If they come out it will be a DQ.

Exempt: Drive shafts, ball joints and other drive train parts that break during the run.

Stopping at end of pit: You must stop at end of pit. Stop must be completed before turning towards& proceeding towards pit area at the fence. If stop is not completed; this will result in a disqualification.

If not allowed to get distance measurement this will result in disqualification.

Others:

2 minute rule: when you are called to the line and are not present you will be put on the 2 minute clock. You will then have 2 minutes to make forward progress to come to the line and race. If you do not show you will then scratch your run.

If you are coming to the line and you are shut down due to official time out or red light you will have 5 minutes to make forward progress coming to the line or to get the vehicle started if sitting on the line after being called back to the line.

If truck breaks at line you have 1 chance to try again(2 min. rule). In running order.

If 20 foot mark is not broken you have 1 chance to try again(2 min. rule). In running order.

All final decision are upon officials discretion.

Open

Engine-	Allowed:	any type
Carburetion-	Allowed:	any type
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	allowed:	any type
Frame:	allowed:	any type
Axles-	allowed:	any type
Suspension-	allowed:	any type
Exhaust-	must be:	not aimed at spectators or officials
	Allowed:	open
Fuel-	must be:	safe & stable
	Allowed:	any type
Tires-	Allowed:	any type
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes
Drive train-	must be:	Driveshaft loops. One per shaft.
Roll cage-	Must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame. Unsafe cage.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.

* see general rules

35" pure stock (page 1)

Engine-	Must be:	original equip. for make(ford in ford, chevy in chevy). Motor type location. cast iron block & heads.
v-8	Allowed:	big block in half ton and heavier trucks. Aluminum intake. V-8 in any truck that offered a from factory.
trucks	Not allowed:	relocating engine. Aluminum heads. Aluminum block. Big blocks in any mini/ compact
Carburetion-	Must be:	single carb or stock efi if applicable to make & model
	Allowed:	aluminum intake & spacers, aftermarket carburetors.
	Not allowed:	after market injection. Blowers. Superchargers.
Body (interior)-	Must be:	firewall & floorboard in stock location & made of factory type material. All interior panels, seats & all dash intact in cab.
	Allowed:	Race seats & race harnesses.
	Not allowed:	cutting & gutting. Loose items.
Body (exterior)-	must be:	full body vehicles. All lights & glass must be present.
	Allowed:	removal of body parts that can be removed; top of jeep, blazer etc. with same features may be removed. Fender trim for tire fitment only. Flat bed(has to be able to support 300 lbs at any point on bed)
	Not allowed:	lexan windows. Cutting & gutting. Body swaps. Fiberglass bodies.
Frame:	must be:	o.e. stock frame that matches make of body.
	Not allowed:	modified frames. Cutting. Tube frames.
Axles-	must be:	in stock location & fender well location.
	Allowed:	axle upgrade
	Not allowed:	wheel base alterations
Suspension-	must be:	stock
	Allowed:	lift kits- ladder bars
	Not allowed:	coil over shocks. 3 & 4 link suspension. Floating suspension. Relocating.
Drive train-	must be:	stock transfer case. Stock transmission.
	Not allowed:	aftermarket transfer case or chain drives.
Exhaust-	must be:	full exhaust. 12" minimum muffler. Pipes come within 1 foot of rear axle or 18" past drivers compartment.
	Allowed:	up to 3 ½ " max diameter exhaust pipe. Headers.
	Not allowed:	open exhaust or Dumps.

35" pure stock (page 2)

Fuel-	must be:	unleaded pump gas only.
	Allowed:	fuel cells. 3/8 fuel line or smaller.
	Not allowed:	race fuel. Alcohol. Will check for dye. No nitrous. Regulators. Adjustable fuel logs.
Fuel pump-	must be:	stock manual fuel pump only.
	Allowed:	stock efi fuel pump running stock efi.
	Not allowed:	efi fuel pump assisting manual fuel pump or anything besides stock efi. Regulators. Adjustable fuel logs.
Tires-	must be:	35" & below dot
	Allowed:	dot tires measuring up to 35"
	Not allowed:	cut tires. Modified tires. Ag tires. Paddle tires.
Brakes-	must be:	have all 4 brakes on both axles & in working order.
	Not allowed:	trans brake braking system & driveline brakes. Transmission break.
Additional-	must be:	battery in stock location. Radiator in stock location. All topless vehicles must have roll cage & five point harness.
	Roll cage exemption:	any truck that qualifies for pure stock 35" class or 38.5" class does not have to have roll cage. Can only change tires to run upper classes.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
		* see general rules

37" super stock (page 1)

Engine-	Must be:	natural aspirated
	Allowed:	aluminum heads & intake
	Not allowed:	aluminum blocks. harmonic balancer cannot be behind front axle tube.
Carburetion-	must be:	single carbs
	Allowed:	aftermarket carb
	Not allowed:	aftermarket injection. Blowers. Superchargers. Nitrous. Dual carbs.
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	cab & o.e. frame minimum. Windshield minimum. Must resemble a vehicle
	Allowed:	cutting & gutting
	Not allowed:	loose items
Frame:	must be:	o.e. frame
	Allowed:	Lightning of frame.
	Not allowed:	Tube frame.
Axles-	must be:	front axle cannot be in front of harmonic balancer.
	Allowed:	supports, ladder bars & other axle supports.
Suspension-	must be:	stock type suspension. One leaf spring minimum installed & functional on each corner. Suspension will be determined off make of body or frame.
	Allowed:	one leaf spring per side hooked to axle & frame. Functional springs. Coil overs along with stock type suspension. Fiberglass leaf springs.
	Not allowed:	3 & 4 link. Floaters. Wishbone & anything else that is not stock truck type suspension
Exhaust-	must be:	aimed away from spectators, officials. Safe.
	Allowed:	open exhaust
Fuel-	must be:	safe & controlled
	Allowed:	race fuel & alcohol
	Not allowed:	nitrous. nitrous bottle in vehicle.

37" super stock (page 2)

Tires-	must be:	37" & below dot tires
	Allowed:	dot 37" & below tires
	Not allowed:	cut tires. Ag tires. Paddle tires. Modified tires.
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes
Drive train-	must be:	transfer case. Driveshaft loops. One per shaft.
	Allowed:	after market transfer case
	Not allowed:	chain drives
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame.

Added safety requirements- Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.

* see general rules.

38.5" pure stock (page 1)

Engine-	must be:	original equip. for make(ford in ford, chevy in chevy). Motor type must be offered in make and model. Stock location. Radiator stock location. cast iron block & heads
	Allowed:	big block in half ton and heavier trucks. Aluminum intake. V-8 in any truck that offered a v-8 from factory.
	Not allowed:	relocating engine. Aluminum heads. Aluminum block. Big blocks in any mini/ compact trucks
Carburetion-	must be:	single carb or stock efi if applicable to make & model
	Allowed:	aluminum intake & spacers, aftermarket carburetors.
	Not allowed:	after market injection. Blowers. Superchargers.
Body (interior)-	must be:	firewall & floorboard in stock location & made of factory type material. All interior panels, seats & all dash intact in cab.
	Allowed:	Race seats & race harnesses.
	Not allowed:	cutting & gutting. Loose items.
Body (exterior)-	must be:	full body vehicles. All lights & glass must be present.
	Allowed:	removal of body parts that can be removed; top of jeep, blazer etc. with same features may be removed. Fender trim for tire fitment only. Flat bed(has to be able to support 300 lbs at any point on bed)
	Not allowed:	lexan windows. Cutting & gutting. Body swaps. Fiberglass bodies.
Frame:	must be:	o.e. stock frame that matches make of body.
	Not allowed:	modified frames. Cutting. Tube frames.
Axles-	must be:	in stock location & fender well location.
	Allowed:	axle upgrade
	Not allowed:	wheel base alterations
Suspension-	must be:	stock
	Allowed:	lift kits- ladder bars
	Not allowed:	coil over shocks. 3 & 4 link suspension. Floating suspension. Relocating.
Drive train-	must be:	stock transfer case. Stock transmission.
	Not allowed:	aftermarket transfer case or chain drives.
Exhaust-	must be:	full exhaust. 12" minimum muffler. Pipes come within 1 foot of rear axle or 18" past drivers compartment.
	Allowed:	up to 3 ½ " max diameter exhaust pipe. Headers.
	Not allowed:	open exhaust or Dumps.

38.5" pure stock (page 2)

Fuel-	must be:	unleaded pump gas only.
	Allowed:	fuel cells. 3/8 fuel line or smaller.
	Not allowed:	race fuel. Alcohol. Will check for dye. No nitrous. Regulators. Adjustable fuel logs.
Fuel pump-	must be:	stock manual fuel pump only.
	Allowed:	stock efi fuel pump running stock efi.
	Not allowed:	efi fuel pump assisting manual fuel pump or anything besides stock efi. Regulators. Adjustable fuel logs.
Tires-	must be:	38.5" & below dot
	Allowed:	dot tires measuring up to 38.5"
	Not allowed:	cut tires. Modified tires. Ag tires. Paddle tires.
Brakes-	must be:	have all 4 brakes on both axles & in working order.
	Not allowed:	trans brake braking system & driveline brakes. Transmission break.
Additional-	must be:	battery in stock location. Radiator in stock location. All topless vehicles must have roll cage & five point harness.
	Roll cage exemption:	any truck that qualifies for pure stock 35" class or 38.5" class does not have to have roll cage. Can only change tires to run upper classes.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
		* see general rules

40" super stock (page 1)

Engine-	must be:	natural aspirated
	Allowed:	aluminum heads & intake
	Not allowed:	aluminum blocks. harmonic balancer cannot be behind front axle tube.
Carburetion-	must be:	single carbs
	Allowed:	aftermarket carb
	Not allowed:	aftermarket injection. Blowers. Superchargers. Nitrous. Dual carbs.
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	cab & o.e. frame minimum. Windshield minimum. Must resemble a vehicle
	Allowed:	cutting & gutting
	Not allowed:	loose items
Frame-	must be:	o.e. frame
	Allowed:	Lightning of frame.
	Not allowed:	Tube frame.
Axles-	must be:	front axle cannot be in front of harmonic balancer.
Suspension-	must be:	stock type suspension. One leaf spring minimum installed & functional on each corner. Suspension will be determined off make of body or frame.
	Allowed:	one leaf spring per side hooked to axle & frame. Functional springs. Coil overs along with stock type suspension. Fiberglass leaf springs.
	Not allowed:	3 & 4 link. Floaters. Wishbone & anything else that is not stock truck type suspension.
Exhaust-	must be:	aimed away from spectators, officials
	Allowed:	open exhaust
Fuel-	must be:	safe & controlled
	Allowed:	race fuel & alcohol
	Not allowed:	nitrous. nitrous bottle in vehicle

40" super stock (page 2)

Tires-	must be:	40" & below dot tires
	Allowed:	dot 40" & below tires
	Not allowed:	cut tires. Ag tires. Paddle tires. Modified tires.
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes
Drive train-	must be:	transfer case. Driveshaft loops. One per shaft.
	Allowed:	after market transfer case
	Not allowed:	chain drives
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.

* see general rules.

44" super modified mens <44" super modified womens-same as men except woman driver> (page 1)

Engine-	must be:	natural aspirated.
	Allowed:	Aluminum heads. Intake. Block.
	Not allowed:	harmonic balancer cannot be behind front axle tube
Carburetion-	must be:	natural aspirated
	Allowed:	nitrous. Aftermarket injection. Aftermarket carburetors. Dual carbs
	Not allowed:	aftermarket turbos. Blowers. Superchargers.
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	cab & o.e. frame minimum. Must resemble a vehicle.
	Allowed:	cutting & gutting
	Not allowed:	loose items
Frame-	must be:	o.e. frame
	Allowed:	lightening of frame
	Not allowed:	Tube frame.
Axles-	must be:	any type. Front axle cannot be in front of harmonic balancer.
Suspension-	must be:	any type
Exhaust-	must be:	aimed away from spectators, officials
	Allowed:	open
Fuel-	must be:	safe & controlled
	Allowed:	any type
	Not allowed:	unsafe fuels
Tires-	must be:	44" & below dot
	Allowed:	44" & below dot
	Not allowed:	ag. Paddle. Cuts. Modified.
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes

44" super modified mens (44" super modified womens-same as men except woman driver) (page 2)

Drive train-	must be:	transfer case. Driveshaft loops. One per shaft.
	Allowed:	after market transfer case
	Not allowed:	chain drives
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame. Unsafe cage.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
* see general rules		

40" modified

Engine-	Allowed:	any type
Carburetion-	must be:	natural aspirated
	Allowed:	dual carbs
	Not allowed:	aftermarket injection. Blowers. Superchargers. Nitrous.
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	cab & o.e. frame minimum. Windshield minimum. Must resemble a vehicle
	Allowed:	cutting & gutting
	Not allowed:	loose items
Frame-	must be:	o.e. frame
	Allowed:	Lightning of frame.
	Not allowed:	Tube frame.
Axles-	Allowed:	any type
Suspension-	Allowed:	any type
Exhaust-	must be:	not aimed at spectators or officials
	Allowed:	open
Fuel-	must be:	safe & stable
	Allowed:	race fuel & alcohol
	Not allowed:	nitrous. Nitrous bottle in vehicle.
Tires-	must be:	40" & below
	Allowed:	any type
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes
Drive train-	must be:	transfer case. Driveshaft loops. One per shaft.
	Allowed:	after market transfer case
	Not allowed:	chain drives
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame. Unsafe cage.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
		*see general rules

outlaws

Engine-	Allowed:	any type
Carburetion-	Allowed:	any type
Body (interior)-	must be:	firewall intact & made from factory thickness or thicker material
	Allowed:	removal of panels, gauges etc.
	Not allowed:	exposed, unsecured battery in cab. Loose items.
Body (exterior)-	must be:	o.e. cab & fenders. Resemble vehicle.
	Allowed:	gutting
Frame-	Allowed:	any type
Axles-	Allowed:	any type
	must be:	
	Allowed:	any type
Suspension-	Allowed:	any type
Exhaust-	must be:	not aimed at spectators or officials
	Allowed:	open
Fuel-	must be:	safe & stable
	Allowed:	any type
	Not allowed:	any type
Tires-	Allowed:	any type
Brakes-	must be:	functional brakes
	Allowed:	drive line
	Not allowed:	unsafe brakes
Drive train-	must be:	Driveshaft loops. One per shaft.
Roll cage-	must be:	4 point roll cage to frame.
	Allowed:	4 point roll cage attached 4 x 4 shear plate attached to frame
	Not allowed:	exhaust pipe. Pvc pipe. Cage not secured to frame. Unsafe cage.
Added safety requirements-		Helmets. Seatbelts. Stop at end of pit. No loose items in vehicle.
* see general rules		